



Three-phase power transformers

IP 23

Type KTK

Power range 125 to 1600 kVA

MAIN FEATURES:

- enclosure class IP 23
- colour RAL 7032
- vacuum impregnation
- crosslaminated core
- small losses
- excellent mechanical durability

The transformers can be manufactured and tested in compliance with the requirements of various standards and classification societies.

Please specify upon ordering:

the type • power • frequency • primary and secondary voltages • manufacturing standards
 • other further details such as intermittent operation, economizing circuits, etc. In case of several secondary voltages, it is usual to also indicate the strength of each voltage and if separate windings will be required.

Three-phase power transformers

IP 23

Type KTK

Power range 125 to 1600 kVA

Rated power		Dim/mm								Weight	Flange
kVA	Core	A	B	C	D	E	F	H	Ø	kg	
125	610	1000	550	498	390	930	620	1150	20	570	2 x D
160	620	1000	550	556	390	930	620	1150	20	745	2 x D
200	630	1000	550	556	390	930	620	1150	20	820	2 x D
250	640	1090	550	580	390	1020	620	1250	20	975	2 x D
315	650	1240	600	710	500	1170	670	1365	20	1280	2 x D
400	660	1240	600	710	500	1170	670	1365	20	1480	2 x D
500	670	1240	730	710	500	1170	800	1565	20	1740	2 x D
630	680	1475	730	870	500	1405	800	1665	20	2210	2 x G*
800	682	1680	1050	780/920	650	1650	1150	1570	20	2790	4 x G*
1000	695	1680	1050	780/920	650	1650	1150	1855	20	3100	4 x G*
1250	702	1680	1050	780/920	650	1650	1150	1855	20	3470	4 x G*
1600	710	1680	1050	780/920	650	1650	1150	2140	20	4450	4 x G*

*) G = 358 x 120 mm

